

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (original) A method for generating a control message to be transmitted from a first network device to a second network device in a data network, the control message relating to an action to be performed at the second network device, the method comprising:

determining a first control message to be generated;

identifying reason information relating to at least one reason for generating the first control message; and

generating the first control message, the first control message including said reason information.

2. (original) The method of claim 1 wherein the first control message corresponds to an Internet Key Exchange protocol control message.

3. (original) The method of claim 1 wherein the first control message corresponds to an IP Security protocol control message.

4. (original) The method of claim 1 wherein the first control message corresponds to an Internet Security Association Key Management Protocol control message.

5. (original) The method of claim 1 wherein the first control message corresponds to a control message used for modifying a security association.

6. (original) The method of claim 1 further comprising transmitting the first control message to the second network device to thereby cause the second network device to implement an appropriate action in response to the first control message.

7. (original) A method for communicating between nodes in a data network, the method comprising:

receiving a first control message from a first node, the control message including reason information relating to at least one reason for the generation of the first control message;

identifying the reason information;
determining an appropriate response to the first control message using at least said reason information; and
implementing said appropriate response.

8. (original) The method of claim 7 wherein the first control message corresponds to an Internet Key Exchange protocol control message.

9. (original) The method of claim 7 wherein the first control message corresponds to an IP Security protocol control message.

10. (original) The method of claim 7 wherein the first control message corresponds to an Internet Security Association Key Management Protocol control message.

11. (original) The method of claim 7 wherein the first control message corresponds to a control message used for modifying a security association.

12. (original) The method of claim 7 further comprising:
implementing a first response to the first control message if the reason information includes a first reason code; and
implementing a second response to the control message if the reason information includes a second reason code.

13. (original) The method of claim 7 wherein the control message relates to an action to be performed at a network device receiving the control message.

14. (original) A computer program product for generating a control message to be transmitted from a first network device to a second network device in a data network, the control message relating to an action to be performed at the second network device, the computer program product comprising:

a computer usable medium having computer readable code embodied therein, the computer readable code comprising:

computer code for determining a first control message to be generated;

computer code for identifying reason information relating to at least one reason for generating the first control message; and

computer code for generating the first control message, the first control message including said reason information.

15. (original) The computer program product of claim 14 wherein the first control message corresponds to an Internet Key Exchange protocol control message.

16. (original) The computer program product of claim 14 wherein the first control message corresponds to an IP Security protocol control message.

17. (original) The computer program product of claim 14 wherein the first control message corresponds to an Internet Security Association Key Management Protocol control message.

18. (original) The computer program product of claim 14 wherein the first control message corresponds to a control message used for modifying a security association.

19. (original) A computer program product for communicating between nodes in a data network, the computer program product comprising:

a computer usable medium having computer readable code embodied therein, the computer readable code comprising:

computer code for receiving a first control message from a first node, the control message including reason information relating to at least one reason for the generation of the first control message;

computer code for identifying the reason information;

computer code for determining an appropriate response to the first control message using at least said reason information; and

computer code for implementing said appropriate response.

20. (original) The computer program product of claim 19 wherein the first control message corresponds to an Internet Key Exchange protocol control message.

21. (original) The computer program product of claim 19 wherein the first control message corresponds to an IP Security protocol control message.

22. (original) The computer program product of claim 19 wherein the first control message corresponds to an Internet Security Association Key Management Protocol control message.

23. (original) The computer program product of claim 19 wherein the first control message corresponds to a control message used for modifying a security association.

24. (original) The computer program product of claim 19 further comprising:
computer code for implementing a first response to the first control message if the reason information includes a first reason code; and
computer code for implementing a second response to the control message if the reason information includes a second reason code.

25. (original) The computer program product of claim 19 wherein the control message relates to an action to be performed at a network device receiving the control message.

26. (original) A system for communicating between nodes in a data network, the system comprising:

means for receiving a first control message from a first node, the control message including reason information relating to at least one reason for the generation of the first control message;

means for identifying the reason information;

means for determining an appropriate response to the first control message using at least said reason information; and

means for implementing said appropriate response.

27. (original) The system of claim 26 wherein the first control message corresponds to an Internet Key Exchange protocol control message.

28. (original) The system of claim 26 wherein the first control message corresponds to an IP Security protocol control message.

29. (original) The system of claim 26 wherein the first control message corresponds to an Internet Security Association Key Management Protocol control message.

30. (original) The system of claim 26 wherein the first control message corresponds to a control message used for modifying a security association.

31. (original) The system of claim 26 further comprising means for transmitting the first control message to the second network device to thereby cause the second network device to implement an appropriate action in response to the first control message.

32. (original) The system of claim 26 further comprising:
means for implementing a first response to the first control message if the reason information includes a first reason code; and
means for implementing a second response to the control message if the reason information includes a second reason code.

33. (original) The system of claim 26 wherein the control message relates to an action to be performed at a network device receiving the control message.

34. (original) A system for generating a control message to be transmitted to a network device in a data network, the control message relating to an action to be performed at the network device, the system comprising:

at least one CPU;
memory; and
at least one interface for communicating with the network device;
the system being configured or designed to determine a first control message to be generated;
the system being further configured or designed to identify reason information relating to at least one reason for generating the first control message; and
the system being further configured or designed to generate the first control message, wherein the first control message includes said reason information.

35. (original) The system of claim 34 wherein the first control message corresponds to an Internet Key Exchange protocol control message.

36. (original) The system of claim 34 wherein the first control message corresponds to an IP Security protocol control message.

37. (original) The system of claim 34 wherein the first control message corresponds to an Internet Security Association Key Management Protocol control message.

38. (original) The system of claim 34 wherein the first control message corresponds to a control message used for modifying a security association.

39. (original) The system of claim 34 being further configured or designed to transmit the first control message to a second network device to thereby cause the second network device to implement an appropriate action in response to the first control message.

40. (original) A system for communicating between nodes in a data network, the system comprising:

- at least one CPU;

- memory; and

- at least one interface for communicating with at least one network device;

- the system being configured or designed to receive a first control message from a first node, the control message including reason information relating to at least one reason for the generation of the first control message;

- the system being further configured or designed to identify the reason information;

- the system being further configured or designed to determine an appropriate response to the first control message using at least said reason information; and

- the system being further configured or designed to implement said appropriate response.

41. (original) The system of claim 40 wherein the first control message corresponds to an Internet Key Exchange protocol control message.

42. (original) The system of claim 40 wherein the first control message corresponds to an IP Security protocol control message.

43. (original) The system of claim 40 wherein the first control message corresponds to an Internet Security Association Key Management Protocol control message.

44. (original) The system of claim 40 wherein the first control message corresponds to a control message used for modifying a security association.

45. (original) The system of claim 40 further comprising:
the system being further configured or designed to implement a first response to the first control message if the reason information includes a first reason code; and
the system being further configured or designed to implement a second response to the control message if the reason information includes a second reason code.